



CHAINS RAISE 1" ABOVE ROLLER SURFACE IN RAISED POSITION, 1/2" BELOW ROLLERS WHEN RETRACTED.

RAISED POSITION

SPECIFICATIONS

| | |
|---|---------------------------------------|
| EFFECTIVE WIDTH (EW): 31" to 61" | BETWEEN LANES (BL): 3" to 12" |
| ELEVATION: 12" top of roller minimum | LENGTH (LG) : 60" to 120" |
| NUMBER OF STRANDS (NS): 2, 3 or 4 | SPEED: 30 - 60 Feet Per Minute |
| ROLLER CENTERS (RC): 4", 4-1/2", 6" | CHAIN CENTERS (TC): 12" to 48" |
| MOTOR: 3/4 HP through 1 HP. Energy efficient and inverter duty motors also available. Voltages include 120/1/60, 230/3/60, 460/3/60, 575/3/60 & DC Voltage. | |
| ROLLER BEARING: Precision ABEC style with 11/16" hexagon axle | |
| CHAIN: #C60, single pitch flat top conveyor chain, 3/4" pitch | |
| AIR REQUIREMENTS: Transfer lift is pneumatically actuated, requires approximately 0.10 Ft ³ of 60 PSI air per lift cycle. Includes FLR unit and (2) position double solenoid valve, 120 volt AC or 24 volt DC coils. | |
| ELECTRICAL REQUIREMENTS: Includes up and down position proximity switches, 20 to 250 volt AC/DC, prewired and terminated in 6" square junction box on outside of conveyor frame. Photo-eye sensor available as option for product detection. | |
| STOP: Fixed or retractable product stops available as an option | |
| ROLLER COVER: Standard roller finish is carbon steel. <u>Options</u> for galvanized steel, urethane covers, or Ultrex accumulation sleeves also available | |
| SUPPORTS: Minimum top of roller elevation is 12", supports available for up to 48" elevation | |
| FRAME FINISH: Standard finish is OSHA safety blue. <u>Optional</u> colors include green, beige, gray, orange, black and yellow | |

Model: T11C25 – Cross Lane Chain Transfer, 1500 pound capacity
 T12C25 – Cross Lane Chain Transfer, 4000 pound capacity

| | |
|-----|--|
| REV | |
| 0 | |